


MOBILE ELEVATING WORK PLATFORM

Offering an electric motor drive configuration, the Pettibone AS2632E mobile elevating work platform provides personnel with a reliable, reinforced lift for safely working indoors at heights up to 32.8 feet.



SPECIFICATIONS



DIMENSIONS	
1 Overall Height	6.4' (195 cm) - rails down 7.6' (232 cm) - rails up
2 Platform Extension	3' (91 cm)
3 Overall Length	7.9' (241 cm)
4 Overall Width	2.7' (82 cm)
Work Height	32.8' (1,000 cm)
Machine Weight	4,718 lbs (2,140 kg)
PERFORMANCE	
Platform Capacity	510 lbs (231 kg)
On-Deck Extension Capacity	265 lbs (120 kg)
Platform Occupants	2 - indoor use only
Drive Speed	Lowered: 2.2 ± 0.12 mph (3.5 ± 0.19 km/h) Elevated: 0.5 ± 0.06 mph (0.8 ± 0.1 km/h)
Lift Time	31 ± 3 seconds
Lower Time	40 ± 3 seconds
Gradeability	25%
Maximum Slope	1.5° / 3°
Maximum Ground Pressure	122.2 psi
Inside Turning Radius	11" (28 cm)
Outside Turning Radius	7' (213 cm)
Standards Compliance	: ANSI A92.20 : CSA-B354.6

FEATURES & OPTIONS

FEATURES

Slope sensor

Optimized electronic control system
Universal drive control box
Proportional control
Quick disconnect for control box
Emergency stop device
Platform power 120VAC (GFCI)
Foot pedal control for platform extension
Fold-in guard rails
Self-closing, self-catching entry gate
Lanyard anchor point
Large scissor arms
Pressure transducer
Full-height drive
Intelligent diagnostic system
Tilt sensor and alarm

Motion alarm
Flashing beacon/buzzer
Emergency descent
Descent alarm and protection
Overload alarm
Horn/hour meter
4x2 drive
Extra wide, non-marking tires
Pothole guards
Two-wheel brake
Manual brake release
Advanced battery charger with voltage
protection
Slide-out component tray
Charging status indicator

Charging operation limit



PETTIBONE. LLC

1100 Superior Avenue Baraga, MI 49908

P: 906.379.4529 info@gopettibone.com www.gopettibone.com

		WAKKANIY
	1 Year	Full machine and attachment
1-2-5 WARRANTY	2 Years or 2,000 hrs	Electric drive motor
	5 Years	Frame weldment, scissor stacks & platform weldment

WADDANTV

^{*} Specifications are subject to change.